Cost Reduction Potential of Polymeric Collectors



Michaela Meir

Aventa AS


Journée R&D ADEME Sophia Antipolis, France

26 April 2018





Main differences to solar heating systems with conventional flat plate collectors



Main differences to solar heating systems with conventional flat plate collectors




Collector

- High-temperature performance polymers
- Flexible lengths
- Light-weight building modules (8 kg/m²)
- Replacing conventional building envelopes (roofs & facades)





Main differences to solar heating systems with conventional flat plate collectors



Collector

- High-temperature performance polymers
- Flexible lengths
- Light-weight building modules (8 kg/m²)
- Replacing conventional building envelopes (roofs & facades)

System

- Water as heat carrier
- High-flow system
- Drain-back technology
- Non-pressurized collector loop (installation)





Major Production Steps

Structured sheet extrusion



■ The number of production steps is significantly reduced compared to conventional solar collector production.



End-cap assembly and coating










Cutting

Absorber production

- Highly-industrialised processing
- Very few production steps
- Low production costs with high volume
- Integrated design











Weight of components, Solar combisystem

Average value of material (kg)
"Combisystems 2008" with
Conventional flat-plate collector





Material weight comparison (in kg) Combisystem, Housing Estate Oslo: **Polymeric AventaSolar collector**







Solar Thermal Value Chain

No wholesaler / distributor!









1. Architecture + Energy Consultant

2. Production

3. Distribution Transport

4. Installation

5. Installed System 6. Operation and Maintenance

7. LCOHs










Prices of solar heating systems in private homes

■ Total end-user costs incl. solar collector system and heat store, reported by the customers, include installation, but exclude VAT and subsidies.






Cost examples: Medium-sized projects (1)

Ilseng State Prison

Costs:

Solar collector, heat store, pumps, control system, pipes, removal of tiles, installation, engineering and administration.

SUM: 433 €/m² collector area









Cost examples: Medium-sized projects (2)

Bjørkelangen Elementary School

Solar heating system for domestic hot water preparation. 105 m² facade integrated solar collectors 5.6 m³ heat buffer store

Costs

Solar collector, heat store, pipes and controller, incl. installation: SUM: 370 €/m² collector area

Savings due to replacement of other materials/components are not included.















Cost examples: Solar combisystem (3)

Housing Estate Oslo with 34 passive houses



34 houses with totally 480 m² roof integrated solar collectors, decentralized with 0.8 m³ heat stores, incl.100 liters DHW preheater and piping, operation control of the auxiliary heat supply and solar heating system, installation- and start-up support.

Costs


SUM: 370 €/m² collector area







Examples, Norway









Ilseng State Prison

Retrofit, DHW preparation 237 m² Collector area 8.4 m³ Heat store 1100 kWh/(m² a) solar irradiance*

Bjørkelangen Elementary School

New-built, DHW preparation 105 m² Collector area 5.6 m³ Heat store 889 kWh/(m² a) solar irradiance*


Housing Estate Oslo, 34 passive houses

New-built, Solar combisystems with each 14 m² Collector area 0.8 m³ Heat store 1210 kWh/(m² a) solar irradiance*

* Solar irradiance on tilted collector surface.



Examples, Norway



Lifetime 20 years







Ilseng State Prison

Retrofit, DHW preparation 237 m² Collector area 8.4 m³ Heat store 1100 kWh/(m² a) solar irradiance*

LCoHs_retrofit = 0.099 €/kWh LCoHs new built = 0.073 €/kWh

Bjørkelangen Elementary School

New-built, DHW preparation 105 m² Collector area 5.6 m³ Heat store 889 kWh/(m² a) solar irradiance*

LCoHs = 0.035 €/kWh

Housing Estate Oslo, 34 passive houses

New-built, Solar combisystems with each 14 m² Collector area 0.8 m³ Heat store 1210 kWh/(m² a) solar irradiance*

LCoHs = 0.082 €/kWh

Electricity costs = 0.115 €/kWh

Comments:

- Retrofit: roof tiles had to be removed
- * Søleri I diadignise on i telltette del trotward fa east
- High solar fraction

Comments:

Good planning, infrastructure

Comments:

- Passive houses: designed for high solar fraction
- Installation partly included



Thank you for your attention!

Aventa AS

Michaela Meir

www.aventasolar.com

mm@aventa.no



